



KMR

The partner for craftsmanship

Strip magazine nailer 3533-0000

12100567



KMR Strip nails D34°

Diameter 2,8 - 3,4 mm

Length 64 - 100 mm

Properties:

- with penetration depth adjustment
- handy
- sturdy

Applications:

Timber engineers, carpentry companies, roofers. e.g. for battens, panelling, boarding, frame construction



4 045759 054184


TECHNICAL DATA

Type Description	3533
Article code	12100567
Height/Length in mm	363/353
Weight	3,6 kg
Magazine type	Rear loader
Safety system	Switchable single to contact actuation
Fastener type	KMR Strip nails D34°
Diameter	2,8 - 3,4 mm
Length	64 - 100 mm
Magazine capacity	min 56 Nails
Recommended operating pressure	6,0-8,0 bar / 0,60-0,80 Mpa
Maximum permissible air pressure	8,0 bar / 0,8 Mpa
Air consumption per operation	2,9 liter by 6 bar (0,6 MPa)
Inner hose diameter for air supply	9 -10 mm Nominal diameter
Emission sound pressure level at workstation	L pA, 1s = 94 dB (A)
Single-shot emission sound pressure level	L Wa, 1s = 103 dB (A)
Vibration level as per ISO 8862-11 is	3,15m/s ²

Subject to technical modifications

www.kmr-group.eu

Joh. Friedrich Behrens AG, Tel. +49 (0) 4102 78 - 445, info@kmr-group.eu



KMR Strip nails D34°
 Diameter 2,8 - 3,4 mm
 Length 64 - 100 mm



Description	d x L (mm)			MI/CAR	MI/PAL	Code
KMR Strip nails D34° Ring shank	2,8 x 75	HZ	BK	4	192	10401604
KMR Strip nails D34° Smooth shank	3,1 x 80	H	BK	3	144	10401609
KMR Strip nails D34° Smooth shank	3,1 x 90	H	BK	3	144	10401611
KMR Strip nails D34° Smooth shank	3,1 x 90	HZ	GALV	3	144	10401612
KMR Strip nails D34° Ring shank	3,1 x 90	HZ	FV	3	144	10401614
KMR Strip nails D34° Smooth shank	3,4 x 100	H	BK	3	144	10401615
KMR Strip nails D34° Smooth shank	2,8 x 64	H	NK	5	240	10401654
KMR Strip nails D34° Smooth shank	2,8 x 70	HZ	GALV	5	240	10401703
KMR Strip nails D34° Smooth shank	2,8 x 80	HZ	GALV	3	144	10401704
KMR Strip nails D34° Ring shank	2,8 x 70	HZ	BK	5	240	10401715
KMR Strip nails D34° Ring shank	3,1 x 90	HZ	BK	3	144	10401716
KMR Strip nails D34° Smooth shank	3,1 x 90	HZ	BK	2,2	158,4	10401725



Other types and dimensions available upon request

REFERENCES

A2 = stainless steel | A4 = acid resistant, stainless steel | BK = steel, bright | BS = drill point | CP = chisel point | DP = divergent point
 FV = steel, hot-dipped galvanised | GALV = galvanised | H = resinated | LK = oval head | GK = Gas cartridge | PHO = phosphated

CE Information can be found on our website www.kmreich.com

www.kmr-group.eu

Joh. Friedrich Behrens AG, Tel. +49 (0) 4102 78 - 445, info@kmr-group.eu