SPITFIRE P370 C60





In accordance to: EN 15895+A1: 2018 EN 12549 Directive Tool: 2006/42/EC Loads: 2013/29/UE EN 16264

Tool specifications	
Spitfire P370 C60	
350	
3.2	
450/69/240	
6.3/10 (10 loads per disc)	
Brown, Green, Yellow, Red	
10 in magazine (1 strip)	
15 to 60 in strip	

Characteristics

Automatic piston return by rubber spring

Universal fully automatic tool (1 pin per second with magazine)

Power adjustment by wheel with indicator

Different nose adapters for different application

Safety specifications

CE marking

Indirect action class A1 (A*), velocity < 100 m/s

Complete contact pressure necessary to generate the shot

Shock energy absorber for comfort

Easy and quick maintenance

Window for checking cartridge presence

Noise level at operator, EN 12549: LWA,1s = 110 dB(A) / LpA,1s,0 = 106 dB(A) / Lp Cpeak = 144 dB(C)

Vibration: < 2.5 m.s⁻²

Accessories	Consumables	
Single shot	C9, CR9, CR9P, SC9, SBR9, SA9, CT30, C9 clip A, Shuttering spacer, Formwork spacer, metal P-CLIP, CR9TP	
Magazine	C9, SC9 (15 to 60 mm in strip), metal P-CLIP	
Kit CI 50 to 120	CI-6 (up to 120 mm)	

